

**ACNC/TOTALPLEX®**

**DOORBELL FON™**

**DP-28WT**

TODAYS GENERATION DOOR BELL

### **DESCRIPTION**

The 21<sup>st</sup> Century door-answering device is here. Bring ***Convenience, Security & Assistance*** to your home today with the **DOORBELL FON™**. This amazing product allows users to answer a door or gate from any telephone in their home or business. It installs using a single pair of wire for (power, control, signaling & voice). Add on components install on same single pair of wire. Operation is simple. ***No Programming! No Codes!*** Just pick up the telephone like a regular phone call.

### **FEATURES**

- Rugged Space Age polymer casing
- Mounts directly on any Surface
- Installs using single pair of wire
- Operates two separate entryways
- Distinctive ring for each entryway
- Built in call-waiting

### **APPLICATIONS**

- Front/back door
- Driveway Gates
- Remote Entryways
- Delivery Docks
- Marine Docks
- Secured Facilities
- Senior Housing
- Disabled Housing

### **OPERATION**

Simple, when a visitor presses the button on the door box, the telephones will ring with a distinctive ring to let you know someone is at the door. Just simply pick up the telephone and you are automatically connected to that door. If you are on the telephone and a visitor comes to your door you will hear a distinctive call-waiting tone. Press the "flash" key or hook switch your telephone and the built in call-waiting on your **DOORBELL FON™** will switch you to the door and place your outside call on hold. When you are finished talking to the door just press the "flash" key or hook switch and connect back to the outside call.

### **SPECIFICATIONS**

*Design-*

Trim Line Styling

**Power-**

117VA/60Hz 0.1 amp 12 watt

**Output-**

17-28 Volt (talking)

75-vrms/25+/- 2Hz (ringing)

**Construction-**

Rugged polymer casing and mounting bracket

Mylar shielded speaker/microphone

**Mounting-**

Surface mount design

**Operating Temperature-**

-20° F to +120° F

Relative Humidity 95%

Water Drop = .025mm

**MODULAR ADD ON COMPONENTS**

**DP28SW Outbound Relay Trigger Controller**

Provides dry contact closure off star (\*) key on telephone to operate an electrical device.

**DP28NWT Additional door box**

Used for additional entryways

**DP28CI Inbound Relay Trigger Controller**

Provides dry momentary contact closure from the push button on the door box. Great add on for a door chime, camera or light.

**MOUNTING**

**HOOK UP**

